Neoway:有方

N720

LTE module





Qualcomm chipset



Multi-Mode






Operating temperature -40 to +85°C



Smallest size







N720 series is Neoway's new generation of LTE category-4 module, optimized specially for M2M and IoT applications.

Specifications

- GSM/GPRS/EDGE & &CDMA2000®1x/ 1xAdvanced/1xEV-DOrA & &WCDMA R99 to DC-HSPA+&&TD-SCDMA&<E Cat4
- Four Versions support different Bands CN: LTE B1/B3/B5/B8/B38/B39/B40/B41, UMTS B1/B8, TD-SCDMA B34/B39, GSM 900/1800, CDMA BC0
 - EU: LTE B1/B3/B5/B7/B8/B20/B40, UMTS B1/B8. GSM 800/900/1800/1900
 - US: LTE B2/B4/B5/B7/B17, UMTS B2/B4/B5, GSM 800/900/1800/1900
 - JP: LTE B1/B3/B8/B9/B19, UMTS B1/B8/B9/B19
 - CN: China/EU: Europe/JP:Japan
 - US: the United States
- GNSS: GPS /Beidou/Glonass or GPS /Beidou/Galileo
- Conttrol via AT commands: GSM 07.07,07.05 and Neoway enhanced AT commands
- Integrated TCP client & server, UDP,PPP,FTP,HTTP,HTTPS, SMTP,POP3,PING,SSL
- IO voltage: 1.8V
- Supply voltage: 3.3 to 4.3 V (DC), 3.8 V recommended
- Idle current: less than 3 mA
- Package: LGA 100-pin, pitch 1.0 mm
- Dimensions: 30mm*28mm*2.8mm
- Operating temperature: -40 to +85°C

Features

- LTE FDD: non-CA cat4, Max. 150Mbps(DL)/Max 50Mbps(UL) LTE TDD: non-CA cat4, Max. 130Mbps(DL)/Max 35Mbps(UL)
- Control via AT commands: GSM 07.07,07.05 and Neoway enhanced AT commands
- CSD/USSD
- SMS: TEXT/PDU Point to Point/Cell Broadcast
- Voice: PCM
- Firmware update via USB

Enhanced Features

- STK
- **CMUX**
- LBS

Interfaces

- Power, On/Off, Reset
- **USB 2.0**
- **UART**
- 12S
- ADC
- SDIO
- SPI
- SD Card
- SGMII

Highlights


- Compact LGA form factor is ideal for small products with tight space and extended operating temperature range
- GNSS receiver available for applications requiring fast and accurate fixes in any environment
- Worldwide LTE, UMTS/HSPA+ and CDMA2000 1x/GSM/ GPRS/EDGE coverage
- **RNDIS**
- **FOTA**

Certifications

- SRRC
- CCC
- CE
- **FCC**
- RoHS

Applications

- Metering,Logistics
- POS Asset management
- Telematics



2.8mm

MEID:A10000392CDAA8 **(()** () ()

Neoway

W1-2111-1000



IMEI1:862588021280301

N720

CA/C4





4F-2#, LianJian Science&Industry Park, Huarong Road, Longhua sub-district, Shenzhen 518100 P.R.C Tel: +86-755-2967 1361 Fax: +86-755-2967 2566 Copyright © 2016, Neoway Technology Co., Ltd. All rights reserved.

